



## Technical Data Sheet

### FF400LSFROH LOW LOSS 50 OHM ARMoured COAXIAL CABLE

#### Technical Data

<b>PRODUCT NUMBER</b>	<b>60671LSFROH-ARM-5</b>	
LSFROH	LOW SMOKE. FIRE RETARDANT. ZERO HALOGEN	
CONDUCTOR	CONSTITUTION	10 AWG ( 1 / 2.74mm)
	MATERIAL	BARE COPPER CLAD ALUMINIUM WIRE
	MATERIAL	GAS INJECTED FOAMED POLYETHYLENE
INSULATION	THICKNESS	2.25 mm Nom.
	O.D.	7.24 ± 0. 10 mm
	COLOR	NATURAL
SHIELD	FOIL	ADHESIVE AL-MYLAR TAPE IS LONGITUDINALE WRAPPED OVERALL THE CABLE AND ALUMINIUM FOIL FACING OUTWARD.
	BRAND	24 / 8 / 0.16 mm. ALUMINIUM ALLOY WIRES. WITH 92% COVERAGE Min.
	MATERIAL	LSFHPE (80°C. RoHS)
JACKET	THICKNESS	1.08 mm Nom.
	O.D.	10.29 ± 0.30 mm
	COLOR	BLACK
ARMOR	BRAID	24 / 8 / 0.16 mm, STEEL BRAID WIRES, WITH 80% COVERAGE Min.
	MATERIAL	LSFHPE ( 80°C, RoHS )/UV-Resistent
OUTER JACKET	THICKNESS	1.25 mm Nom
	O.D.	13.50 ± 0.30 mm
	COLOR	BLACK
WEIGHT	227.20 Kg / 1 Km	
MARKING	• ... M ..FEEDFLEX® FF400 LSFROH LOW LOSS 50 OHM ARMoured COAXIAL CABLE .. M ... •	

#### PERFORMANCE PROPERTIES

IMPEDANCE	50 ± 2 Ω											
CAPACITANCE	77 pf/m Nom.											
VELOCITY OF PROPAGATION	86% Nom.											
MAX. OPERATING TEMPERATURE. (°C)	-40 / 80°C											
MIN. BEND RADIUS	35.4mm											
ATTENUATION (dB/100m)	MHz	30	50	150	220	450	900	1500	1800	2000	2500	5800
	dB	2.2	2.9	5.0	6.1	8.9	12.8	16.8	18.6	19.6	22.2	35.5
	kW (at 20° C)	3.33	2.58	1.47	1.2	0.83	0.58	0.44	0.4	0.37	0.33	0.21
INNER CONDUCTOR RESISTANCE	4.5 Ω / Km Nom											
INSULATION RESISTANCE	100M Ω-Km Min											
DIELECTRIC STRENGTH	2.5 KV/1min. Min.											

PACKING SIZE IS 500M ON WODDEN DRUM.

## Technical Data Sheet

	ITEM	SPECIFICATION	TEST METHOD	
PROPERTIES of JACKET	SMOKE DENSITY	Dm4 Max. 150	ASTM E662	
	TOXICITY INDEX	Max. 5	NES 713	
	HALOGEN ACID GAS EVOLUTION	0.5% Max.	IEC 60754-1	IEC 60754-2

FLAME RETARDENT ACC. TO IEC 60332-1-2

	CHEMICAL SUBSTANCES	LIMIT OF PMM (mg/kg)	METHOD
PROPERTIES FOR RoHS	LEAD (Pb)	<1000	
	CADMIUM (Cd)	<100	
	MERCURY (Hg)	<1000	
	HEXAVALENT CHROMIUM (Cr <sup>6+</sup> )	<1000	IEC 62321
	POLYBROMINATED BIPHENYL (PBBs)	<1000	
	POLYBROMINATED BIPHENYL (PBDEs)	<1000	

