



NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES)

1. BRASS PER QQ-B-626
2. BRASS PER QQ-B-613
3. NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE
4. NICKEL PL. 200 MIN. THICK OVER COPPER STRIKE
5. GOLD PL. 3 MIN. THICK OVER NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE
6. TEFLON MIL-P-19468

1. CRIMPED FERRULE
HEX CRIMP SIZE .324"
2. CRIMPED CONTACT PIN
HEX CRIMP SIZE .068"

9	FERRULE	NOTE 1	NOTE 3	1	FR-95/85-9/8X127
8	CONTACT PIN	NOTE 1	NOTE 5	1	B1121AA-8-25/19
7	WASHER	NOTE 2	NOTE 3	1	WS-128/9X08
6	RING	SK5	NOTE 4	1	B50000-6
5	RETAINER RING	NOTE 1	NOTE 3	1	B50000-5
4	GASKET	RUBBER	RED	1	GS-115/8X15
3	INSULATOR	NOTE 6	NATURAL	1	B50000-3T-50
2	BODY	NOTE 1	NOTE 3	1	B50000-2-705/52
1	SHELL	NOTE 1	NOTE 3	1	B50000-1-B
NO.	DESCRIPTION	MATERIAL	FINISH	Q'TY	DRAWING NO.

DIMENSIONS ARE IN MILLIMETERS				PART NO.	
UNLESS OTHERWISE SPECIFIED TOLERANCES				APPROVED	DATE
0.5-6 = ±0.2				<i>Alan. W</i>	11-13-03'
6-30 = ±0.4				CHECKED	DATE
30-120 = ±0.6				<i>Alan. W</i>	11-13-03'
120-315 = ±1				DRAWN	DATE
315-1000 = ±1.6				<i>Erma</i>	11-13-03'
1000-2000 = ±2.4				FILE NO. F:\DWG\B\1121AA\5DFB-50\NT3G	

Amphenol
Danbury, CT, USA - Tainan, Taiwan - Shenzhen, China

TITLE: BNC CRIMP PLUG
(FOR 5DFB COAXIAL-HOSIWELL CABLE)

DRAWING NO. B1121AA-NT3G-5DFB-50

ITEM NO. 011121AAG05NA5F

7RD-DR 197968