



Technical Data Sheet

RG59/U COAXIAL CABLE 75 OHM TO MIL-C-17G

Technical Data

PRODUCT NUMBER	FEEDFLEX®	9214
CONDUCTOR	CONSTRUCTION	23 AWG (1 / 0.60 mm)
	MATERIAL	BARE COPPER WIRE
INSULATION	MATERIAL	LDPE
	THICKNESS	1.55 mm Nom.
	O.D.	3.70 ± 0.10 mm
	COLOR	NATURAL
SHIELD	BRAID	16 / 7 / 0.16 mm, BARE COPPER WIRES, WITH 95% COVERAGE Min.
JACKET	MATERIAL	PVC (RoHS)/UV-Resistent
	THICKNESS	0.80 mm Nom.
	O.D.	6.00 ± 0.20 mm
	COLOR	BLACK
WEIGHT		56.0 Kg / 1Km
PRINTING		" ..M .. FEEDFLEX® RG59/U COAXIAL CABLE 75 OHM to MIL-C-17G . . M .."

PERFORMANCE PROPERTIES

IMPEDANCE									
CAPACITANCE									
VELOCITY OF PROPAGATION									
MAX. OPERATING TEMPERATURE. (°C)									
MIN. BEND RADIUS									
ATTENUATION	MHz	10	50	100	200	400	700	900	1000
(dB/100m)	dB	3,6	7.9	11.2	16.1	23.0	31.8	36.4	39.4
AVERAGE POWER	kW (at 20°C)	0.6	0.47	0.31	0.24	0.138	0.1	0.075	0.076
INNER CONDUCTOR RESISTANCE									
INSULATION RESISTANCE									
DIELECTRIC STRENGTH									

